



# ECOGUARD

Best Budget Line Product with Latest Compounding Expertise  
Traditional Pattern Design Brings Customer Reliable Service.

## Unique Features:

1. High Cost-Effective
2. Value For Money

### Available Qualities:

STANDARD COMPOUND



Traditional Classic Pattern Design Built With Super Wear Performance Tread Compound Provide Excellent Service Hours

Tyre Size	Standard Rim	Heel Type		Dimensions (mm)		Load Capacity (kg)					
		Quick	Standard	Section Width	Outer Diameter +/- 2%	Forklift		Other Vehicles			Static (0 km/h)
						Load Wheel 25 km/h	Steer Wheel 25 km/h	6 km/h	10 km/h	25km/h	
5.00-8	3.00D-8	□	◆	130	458	1415	1090	1415	1285	1090	1645
	3.50D-8	□	◆								
18X7-8 (180/70-8)*△	4.33R-8	□	◆	152	457	2145	1650	2145	1945	1650	2490
6.00-9	4.00E-9	□	◆	155	519	1885	1450	1885	1710	1450	2190
21X8-9(200/75-9)*	6.00E-9	□	◆	190	518	2755	2120	2755	2505	2120	3200
	7.00E-9	□	□			2895	2225	2895	2625	2225	3360
6.50-10	5.00F-10	□	◆	165	570	2340	1800	2340	2125	1800	2720
23X9-10 (225/75-10)*	6.50F-10	◆	◆	204	593	3445	2650	3445	3125	2650	4000
7.00-12	5.00S-12	□	◆	174	650	2920	2240	2920	2645	2240	3380
	6.50-12	□	□	245	659	3350	2575	3350	3040	2575	3890
23X10-12 (250/60-12)*	8.00G-12	◆	◆	234	587	3770	2900	3770	3420	2900	4380
8.25-15	6.50-15	□	◆	215	820	4600	3540	4600	4175	3540	5345
28X9-15 (8.15-15)225/75-15	6.50-15	□	□	223	685	3770	2900	3770	3420	2900	4380
	7.00-15	□	◆								
8.25-20	6.50-20	□	□	225	986	4400	3650	4400	3980	3650	5510
	7.00-20	□	□								
	7.50-20	□	□								
9.00-20	6.50-20	□	□	228	989	5400	4500	5400	4905	4500	6795
	7.00-20	□	□								
	7.50-20	□	□								

△ The rim contour may vary from different vehicle manufacturers, please contact with EXMILE technical department for details.

\* Only GV2 is available

□ Under Development

◆ Available